FORTY3 - I Piani - SC043BI


CE EN 14688:2018


 $\textcolor{red}{\textbf{G000}}$ Inspired by $\textcolor{red}{\textbf{Life}}$

Cod. SC043BI

Basin 60.37 h 20 cm. Under-top installation. Weight 12 Kg









CERASLIDE®



BATAFORM®

Cod. FI012BI

Push open valve drain with ceramic top for basins with overflow. Weight 0,5 Kg



Cod. FI012CR

Push open chromed valve drain for basins with overflow. Weight 0,5 Kg









Tips for proper cleaning Ceramic cleaning

We recommend the use of warm water in combination with non-abrasive cleaning products

Click to view or download



DOP N° L001-01



Is the result of years of research, on the glazes and the ceramic application, that ensures more protection, more resistance and ease of cleaning. The careful control of temperatures in the various cooking stages, in a cycle that can last up to 26 hours, ensures perfect homogeneity of the product during the sintering process, reducing porosity and guaranteeing greater resistance against stains, dirt and abrasions.



The antibacterial bataform treatment was developed to ensure deeper hygiene, basing its effectiveness on the reaction of silver ions, which inhibit the proliferation of bacteria. tests carried out by certified laboratories, according to the uni4543 standard, have confirmed a drastic decrease in the presence of bacteria, without however altering the glossy glaze. for cleaning operations, follow the recommendations given for the ceraslide glaze.